

# Gateway Comparison

The Samsara solution includes a number of hardware products and OEM integrations designed to provide the right level of visibility on everything from unpowered assets to complex industrial machinery.



**AG46**

Common Monitoring Use Cases



**AG46P**

Unpowered equipment

Powered equipment



**AG26**

Heavy CAN-based equipment



**IG15**

Heavy CAN-based equipment and sensors



**IG41**

Industrial equipment, sensors, controllers, plus on/off control



**OEM Telematics**

Equipment using JDLink/VisionLink today

## HARDWARE FEATURES

Power	Replaceable battery	Cable and backup battery	Cable and backup battery	Cable and backup battery	Cable	-
Check-in Rate	Default 2x per Day	Real-time when powered	Real-time when powered	Real-time when powered	Real-time when powered	Varies based on JDLink/VisionLink subscription (15 minutes to daily)
Estimated Battery Life (2x Check-ins)	3 years	1 year unpowered	1 year unpowered	1 year unpowered	-	-
Connectivity	LTE-M, 3G, NB-IoT	4G LTE, 3G	4G LTE, 3G	4G LTE, 3G	Dual Carrier 4G LTE, 3G	-
IP-rating	IP69K	IP69K	IP69K	IP69K	IP20	-
Class 1, Division 2 Certified	✓	✓*	✓*	✓*	✓*	-
Enhanced Connectivity	-	-	-	✓	✓	-

## SOFTWARE FEATURES

Location Tracking	✓	✓	✓	✓	✓	✓
Reporting & Alerting	✓	✓	✓	✓	✓	✓
Engine Hours	-	✓	✓	✓	✓	✓
Engine Diagnostics & Fault Codes	-	-	✓	✓	✓	✓
Custom & Client-Facing Dashboards	-	-	-	✓	✓	-
Advanced Alerting	-	-	-	✓	✓	-
Trending Data & Analytics	-	-	-	✓	✓	-
Monitor Third-Party Sensor Data	-	-	-	✓	✓	-
Monitor Controller Data (PLC)	-	-	-	-	✓	-

\*To meet Class 1, Division 2 certification, AG46P, AG26, and IG15 require optional faceplate and IG41 must be in an enclosure

\*\*Requires an active JDLink or VisionLink subscription

Interested in learning more about Samsara?

Contact us today at sales@samsara.com or call (415) 985-2400 for a live demo